




The LZ Liquid Scintillator Screener Campaign

Scott Haselschwardt, for the LZ Collaboration
CoSSURF 2017

May 13, 2017





The LZ Experiment



The LZ Outer Detector

- 9 segmented UVT acrylic tanks
- ~17 tonnes Gd-loaded, LAB-based LS
 - Neutrons thermalize and capture on Gd:
 - $n + \text{Gd} \rightarrow \text{Gd} + (3-4x) \gamma$ (~ 8 MeV)
- 120 8" PMTs in water tank
 - Surrounded by Tyvek reflector
- Together with LXe "skin", veto gammas and neutrons with high efficiency... 100-200 keV threshold
- Reduce WIMP search backgrounds



Simulated neutron background in LZ before and after application of veto cuts



GdLS Purity

- OD rate goal drives scintillator purity requirements
- Usual suspects: ^{238}U chain, ^{232}Th chain & ^{40}K
- ^{14}C (156 keV β) measurement a main concern
 - LLNL Mass Spec down to 10^{-15} g/g
 - Requirement/goal is 10^{-17} - 10^{-18} g/g

Impurity	Goal	Requirement
^{238}U	1.3 ppt	10 ppt
^{232}Th	4.5 ppt	20 ppt
^{40}K	0.8 ppt	3 ppt
^{14}C	1.3×10^{-17} g/g	1.5×10^{-17} g/g

The LS Screener

- Made of Reynolds UVT acrylic (same as OD)
- ~ 24 kg GdLS
 - ~1/700 of OD LS
 - Produced by Minfang Yeh at BNL
- 14 kg water shield
- 3 R11410-20 PMTs
 - Very radiopure
 - LZ PMT bases
- Wrapped in Tyvek reflector



Underground Commissioning, Nov. 2016

Water volume full, mounting PMTs




GdLS filling in underground cleanroom




Ready for Water Tank Deployment

Filled w/ GdLS and water. PMTs mounted:



Teflon tube for
thoron calibration

Wrapped in single layer tyvek, ready for
deployment:




Water Tank Deployment





Data Taking Overview

- Deployed in LUX water shield
 - LUX support stand still present
- Pulses amplified & digitized by LZ electronics
- Run 1: GdLS
 - Mid Nov 2016 – Early Jan 2017
- Run2: No Gd-loading
 - Late Jan 2017 – Late Feb 2017
- ~Weekly PMT gain monitor
- Calibrations end each run:
 - γ : ^{137}Cs , ^{22}Na , ^{40}K , ^{228}Th
 - α & β : Thoron bubbling
- End of each run “z-scan”





Run 1 – First Data

- We see α 's, β 's and Compton deposits from γ 's
- Rate plateau after ~ 3 weeks with ^{222}Rn timescale
- 0.25 phe/keV \rightarrow 3-fold coinc of > 2 phe \rightarrow 24 keV threshold
- Acceptance for $\sim 70\%$ of ^{14}C beta spectrum



Run 2 – No Gd

- Same cocktail without Gd
- Less exposure during LS fill
- Rate plateau after ~ 2 weeks
- Higher light yield, ~0.3 phe/keV






End of Run Z-Scan

- Rate in OD from cavern environment a concern
- End of each run, moved Screener vertically

Wanted to probe here!

Low rate spot



**Top of OD acrylic....
4-5x lower than sim!**


Background Simulations

- Detailed geometry in Geant4-based LUXSim code
- U, Th, K and Co simulated in:
 - Tyvek
 - Ropes
 - Titanium Ballast
 - PMTs and bases
 - PMT mounting structures
 - PMT cabling
 - Flange bolts
 - Acrylic vessel
 - LUX support stand
 - Davis Cavern rock
- In LS volume: U, Th, K, ^{14}C and ^{152}Gd
- Direct screening results or LZ database for normalizations



First Fit to Run 1 Data

- Simulated spectra -> RooFit PDFs grouped by internal or external to LS
- Constraints: External U, Th, K & Co from counting, ^{152}Gd rate from known concentration & late chain U & Th from BiPo rate





Impurity Estimates from Run 1

Impurity	Level Estimate	Comes From	Goal	Requirement
^{238}U	6.5 ± 1.5 ppt early 3.1 ± 0.3 ppt late	Fit early, BiPo late	1.3 ppt	10 ppt
^{232}Th	22 ± 5 ppt early 1.3 ± 0.4 ppt late	Fit early, BiPo late	4.5 ppt	20 ppt
^{40}K	12 ± 1 ppt	Fit	0.8 ppt	3 ppt
^{14}C	$(2.7 \pm 0.1) \times 10^{-17}$ g/g	Fit	1.3×10^{-17} g/g	1.5×10^{-17} g/g

- Close to requirement on ^{14}C
 - Crude fit to Run 2 within factor of 2
- U, Th okay...
 - Evidence for non-equilibrated sub-chains
 - HPGe screening of GdCl_3 underway
- ^{40}K expected to drop with updated fit

Next Steps

- Run 2 fits
- Pulse shape discrimination
 - Constrain U & Th alphas
- Z-scan analysis




Conclusions

- Screener campaign a success!
- Providing useful feedback to LZ
 - Operational experience with GdLS
 - GdLS production modifications for lower backgrounds
- **We are close to our purity requirements for the GdLS**
- **Z-scan constrain Davis Cavern gamma rate**

Thank You!

Dean White
Susanne Kyre
Harry Nelson
Mike Witherell
Curt Nehrkorn
Melih Solmaz
Sally Shaw
Minfang Yeh



Simon Fiorucci
Markus Horn
Dave Taylor
SURF personnel
U. Rochester
Brown U.
U. Davis
LZ Screening Crew



Extra Slides

Thoron Calibration

- Bubble N_2 past ^{228}Th source into LS
- Vents through concentric tubing to bubbler outside water tank



Testing at UCSB

1.06.04 – Gd-LS Impurities 2/20/2017

Yellow are measurements (ICPMS/HPGe), blue screener

Component	Raw Values (ppt)				Gram per Liter Gd-LS	0.1% Gd-LS in veto (ppt)			
	²³⁸ U	²³² Th	⁴⁰ K	¹⁴ C		²³⁸ U	²³² Th	⁴⁰ K	¹⁴ C
LAB	0.004	0.007	0.5	12×10^{-6}	860	0.004	0.007	0.5	12×10^{-6}
Gd	100	100	52		0.86	0.17	0.17	0.09	
PPO	150	640	27	110×10^{-6}	3	0.5	2.2	0.09	0.37×10^{-6}
TMHA	180	650	27	140×10^{-6}	3	0.6	2.1	0.09	0.44×10^{-6}
bis-MSB	210	190	50	19×10^{-3}	0.015	0.004	0.003	0.001	0.32×10^{-6}
Total/Goal					867.2	1.3 (<small>≈3.1BiPo</small>)	4.5	0.8	$3 (\approx 27) \times 10^{-6}$
Rate (Hz)						3.75	3.75	3.75	3.75
Requirement						10	20	3	15×10^{-6}
Rate (Hz)						30	17	14	4.3
Daya Bay						20	4	7	

- Daya Bay levels from one-pass purification of Gd and PPO; ⁴⁰K from water or contamination
- ⁸⁵Kr – if like KAMLAND, <20 counts per day