

Materials Screening for the **LUX-ZEPLIN** Experiment

Kelsey Oliver-Mallory (for Paul Scovell)

on behalf of the LZ Collaboration

UCLA Dark Matter 2016





LZ Backgrounds

Irreducible/Physics Backgrounds

- ^{136}Xe double beta decay ER
- solar neutrinos ER
- solar neutrinos NR


Contamination in Detector Components

- <10% physics backgrounds in 5.6 tonne FV

Radon and Dust measurement and control are a major focus of the collaboration, but are not discussed here



LUX-ZEPLIN



PMTs

PMT bases and cables

TPC components

PTFE sheets

Cryostat


Xe target




Techniques

^{238}U Chain


^{238}U Early sub-chain



^{226}Ra sub-chain



^{210}Pb sub-chain



- Mass Spec., NAA
- U/G Ge
- Si PIN
- alpha spectroscopy

How an assay is done?

Early ^{232}Th refers to measures of ^{228}Ra and ^{228}Ac

Late refers to ^{228}Th and below



Techniques

No single assay technique is sufficient

Techniques:


- Gamma ray spectroscopy with ultralow-background high purity germanium detectors (HPGe)
- Neutron activation analysis (NAA)
- Inductively coupled mass spectroscopy (ICP-MS)
- Alpha spectroscopy, optical inspection (surface contamination)
- Rn emanation




Techniques

^{238}U Chain


^{238}U Early sub-chain



^{226}Ra sub-chain



^{210}Pb sub-chain



This talk will focus on
gamma spectroscopy

- Mass Spec.,
- NAA
- U/G Ge
- Si PIN
- alpha spectroscopy

Gamma ray spectroscopy we're most sensitive to gamma lines between ~50-3000 keV



Gamma Spectroscopy



Detector	Site	Depth mwe	Crystal	[U] mBq/kg	[Th] mBq/kg	Status
Chaloner	Boulby	2805	BEGe	0.6	0.2	Online
Mordred	SURF	4300	N-type	0.7	0.7	Install March 2016
Ge-II	UA	0	P-type	4	1.2	Online
Ge-III	UA	0	P-type	4	1.2	Online
Lumpsey	Boulby	2805	Well	0.4	0.3	Online
Lunehead	Boulby	2805	P-type	0.7	0.2	Online
Merlin	LBNL	0	N-type	6.0	8.0	Online
Maeve	SURF/BHUC	4300	P-type	0.1	0.1	Online
SOLO	Soudan /SURF	2200	P-type	0.5	0.2	Moved to BHUC Jan 2016
Morgan	SURF	4300	P-type	0.2	0.2	Online Nov 2015
Wilton	Boulby	2805	BEGe	7.0	4.0	Online



Titanium


Cryostat & field Rings, many Ti and steel samples were assayed. Each sample started as long slab. Pieces were cut at top and middle. Chose Ti sample (TIMET HN3469 Top and Middle)

Assay	U-early mBq/kg	U-Late mBq/kg	Th-early mBq/kg	Th-late mBq/kg	^{60}Co mBq/kg	^{40}K mBq/kg	
Top	<1.6	<0.09	0.28(3)	0.23(2)	<0.02	<0.54	Maeve
Middle	2.9(15)	<0.10	<0.2	0.25(2)	<0.03	<0.68	Maeve





Titanium



Red: Sum 10% pp Solar
Neutrino Signal + 0.2 NR
Yellow: 5% Solar + .05 NR
Green: 3.3% + 0.03 NR

applying ER and NR
analysis rejection factors
of 200 and 2 (99.5% and
50 rejected)



PMT Bases

For the PMT bases all components have been assayed separately for radioactivity, including ^{210}Pb . Components have been identified with adequately low levels of U, Th, K contamination.

PMT Bases	^{238}U -early mBq/kg	^{238}U -late mBq/kg	^{210}Pb mBq/kg	^{232}Th mBq/kg	^{40}K mBq/kg	^{60}Co mBq/kg	
R8520	338.4	85.78	6863.8	28.23	159.43	4.12	Chaloner
R11410	230.23	77.10	5320.2	28.51	96.89	2.69	Chaloner






Figure 2: KEMET Type C - X7R Dielectric [\[datasheet\]](#)



Boulby 'well' detector







PMT Materials

- The raw PMT materials, that will be used by Hamamatsu, have been assayed and they have sufficiently low contamination
- After the PMTs have been finished they will be assayed again to confirm as-built levels of contamination

Name	U-early mBq/kg	U-late mBq/kg	Th-early mBq/kg	Th-late mBq/kg	⁶⁰ Co mBq/kg	⁴⁰ K mBq/kg
Mass Weighted Average	57.15	2.94	2.94	2.53	2.52	16.56








PTFE NAA

- PTFE requires NAA to achieve the required sensitivity
- UA group completed NAA and found the PTFE was high quality
- Additional R&D being performed to confirm ^{210}Pb levels in the PTFE raw materials

Sample	UA302 PTFE8764	UA303 DuPont 807NX	UA304 DuPont NXT85	UA305 Flontech FLON008
Th [pg/g]	3.13 ± 0.62	7.18 ± 0.48	6.94 ± 0.53	12.60 ± 0.79
U [pg/g]	0.90 ± 1.55 <3.44(90% CL)	3.11 ± 0.73	-0.07 ± 1.08 < 1.70(90% CL)	-0.89 ± 1.88 < 2.19(90% CL)





Intrinsic Contamination

Status, identified all principle materials for building LZ:



- Ti - material identified well below goal
- PMT Bases - all components assayed, [U,Th, K, Co] at or below goals
- PMT - all raw materials assayed, [U,Th, K, Co] at or below goals
- PTFE – initial NAA performed, following EXOs success, [U,Th, K, Co] at or below goals

Continuing to screen for quality control

Will screen completed components as they are finished



SURF & BOULBY: Low Background Assay Labs





Black Hills Underground Campus

- MAEVE/MORGAN relocated from Davis in November. (**ready for samples**)
- SOLO moved from Soudan (Jan 2016)
- MORDRED upgrading to low background detector (likely March 2016)



Initial Assembly of Maeve and Morgan



Black Hills Underground Campus



Liquid nitrogen system and computer control
D. Taylor (SURF),
K. Oliver-Mallory (UCB/LBL),
Danny Johnson (SURF intern)



- Runs independently
- Collaborative site



Black Hills Underground Campus

Open to accepting and screening samples for other people

Contact Keenan Thomas (kjthomas@lbl.gov) for information on obtaining assay services



Maeve and Morgan completed, Mordred shield partially assembled



Summary

- Good progress on high priority items: Ti, PMTs, PMT bases.
 - Overall the estimates are very encouraging
 - Many Requirements already met
 - On schedule with major milestones
- NAA work initiated, leveraging EXO expertise, yielding adequate levels of U, Th.
- ICP-MS assays at UCL anticipated early in 2016 to confirm many of the direct counting results for top-of-chain U and Th.
- On-schedule for completing all direct counting of LZ components to meet construction schedule.



backups




Long-lived decay species & chains with α , β , γ , & n emissions: U, Th, K, Co, ...

All materials contain trace contamination. Some are in secular equilibrium, others are not. Chains pass through a noble gas, **Rn**.

Principal Gamma Ray Lines			
	keV	$P_{\gamma} \times 100$	
^{234}Th	49.55	22.46	^{214}Po 609.312 45.49
^{234}Pa	29.50	5.4	665.453 1.530
	63.30	5.27	768.356 4.892
	92.38	13.7	806.174 1.262
^{234}U	92.80	2.47	934.061 3.10
	43.49	1.414m	1120.29 14.91
	810.3	0.72m	1155.19 1.635
	1001.441	0.856m	1238.11 5.831
	34.30	8.4g	1377.67 3.968
	43.49	86g	2204.21 4.913
	152.71	18.8g	^{210}Bi 46.539 4.252
	227.25	18.4g	
	569.7	10.9g	
	733.56	7.6g	
	883.66	9.8g	
^{238}Rn	186.2	3.55	

^{238}U Decay to ^{206}Pb

Alpha Decays			
	keV	%	Levels
^{238}U	4198	77.54	0 to 0
	4151	22.33	0 to 1
^{234}U	4774.6	71.37	0 to 0
	4722.4	28.42	0 to 1
^{230}Th	4687.6	76.3	0 to 0
	4621.1	23.4	0 to 1
^{226}Ra	4784.34	94.038	0 to 0
	4601.	5.95	0 to 1
^{222}Rn	5489.48	99.882	0 to 0
^{218}Po	6002.35	99.9769	0 to 0
^{214}Po	7686.82	99.9895	0 to 0
^{210}Po	5304.33	99.9988	0 to 0




^{232}Th Decay to ^{208}Pb

Principal Gamma Ray Lines

	keV	$P_{\gamma} \times 100$
^{232}Th	63.811	21.1
^{228}Ra	6.28	12
	6.67	89
	12.88	2.3
	13.52	11.0
	26.40	28
^{228}Ac	57.759	7.25
	338.319	11.72
	911.209	26.5
	968.968	16.1
	1588.19	53.06
^{228}Th	84.373	26.4
^{228}Ra	240.986	5.26
^{212}Pb	115.183	4.87
	238.632	81.6
	300.089	4.66
^{212}Bi	39.858	26.0
	727.33	6.74
	785.37	1.1
^{208}Tl	277.37	10.1
	510.74	24.8
	583.187	86.7
	860.53	12.7
	2614.51	100

Alpha Decays

	keV	%	Levels
^{232}Th	3948.5	21.0	0 to 1
	4011.2	78.9	0 to 0
^{228}Th	5340.35	26.0	0 to 1
	5423.24	73.4	0 to 0
^{224}Ra	5448.80	5.25	0 to 1
	5685.48	94.73	0 to 0
^{220}Rn	6288.22	99.882	0 to 0
^{216}Po	6778.4	99.998	0 to 0
^{212}Bi	5768.29	0.61	0 to 2
	6051.04	25.1	0 to 1
	6090.14	9.7	0 to 0
^{212}Po	8785.17	100	0 to 0



γ -assay can determine 'top and bottom' of chains. Other techniques only the top forcing assumptions about equilibrium



Background Summary

Intrinsic Contamination

Intrinsic Contamination Backgrounds	Mass (kg)	Composite	U early (mBq/kg)	U late (mBq/kg)	Th early (mBq/kg)	Th late (mBq/kg)	Co60 (mBq/kg)	K40 (mBq/kg)	n/yr (inc. S.F. rej.)	ER (cts)	NR (cts) (w/ SF rej.)	NR (cts)	WBS	Name	Assay verified	Signoff Bkgs	Signoff WBS1.10
Upper PMT Structure	40.2	Y	3.86	0.23	0.49	0.38	0.13	1.45	2.25	0.03	0.001	0.004	1.5	Saba	N	N	N
Lower PMT Structure	64.1	Y	2.40	0.13	0.29	0.23	0.07	0.90	4.45	0.02	0.002	0.005	1.5	Saba	N	N	N
R 11410 3" PMTs	93.7	Y	67.08	2.68	2.01	2.01	3.86	62.05	71.96	1.24	0.033	0.085	1.5	Gaitskell	N	N	N
R11410 PMT Bases *	2.6	Y	230.23	77.10	28.51	24.53	2.69	96.89	41.02	0.14	0.019	0.030	1.5	Araujo	N	N	N
R8520 Skin 1" PMTs	4.2	Y	60.50	5.19	4.75	4.75	24.20	332.76	8.90	0.09	0.001	0.002	1.5	Gaitskell	N	N	N
R8520 Skin PMT Bases *	0.6	Y	311.10	80.26	33.42	25.94	3.88	147.54	12.29	0.05	0.002	0.003	1.5	Araujo	N	N	N
PMT Cabling	85.5	Y	29.83	1.47	3.31	3.15	0.65	33.14	2.13	0.82	0.000	0.007	1.5	Gaitskell	N	N	N
TPC PTFE	275.0	N	0.02	0.02	0.01	0.01	0.00	0.10	19.14	0.17	0.007	0.007	1.5	Webb	N	N	N
Grid Wires	0.75	N	1.20	0.27	0.33	0.49	1.60	0.40	0.02	0.01	0.000	0.000	1.5	Webb	N	N	N
Grid Holders	62.2	Y	1.20	0.27	0.33	0.49	1.60	0.40	6.33	0.07	0.003	0.004	1.5	Webb	N	N	N
Field Shaping Rings	91.6	Y	4.79	0.86	0.80	0.75	0.00	1.21	38.83	1.85	0.013	0.018	1.5	Webb	N	N	N
TPC Sensors	0.90	Y	10.64	9.06	9.99	3.07	0.46	15.24	0.57	0.15	0.000	0.000	1.5	Kraus	N	N	N
TPC Thermometers	0.70	Y	331.93	328.68	135.86	135.86	4.90	657.88	77.32	4.58	0.026	0.029	1.5	Kraus	N	N	N
Xe Recirculation Tubing	15.1	Y	0.79	0.18	0.22	0.323	1.05	0.30	0.36	0.01	0.000	0.000	1.5	Shutt	N	N	N
HV Conduits and Cables	137.7	Y	1.8	2.0	0.5	0.6	1.4	1.2	7.2	0.64	0.001	0.001	1.5	McKinsey	N	N	N
HX and PMT Conduits	199.6	Y	1.25	0.40	2.59	0.66	1.24	1.47	5.27	0.46	0.000	0.001	1.3	Taylor	N	N	N
Cryostat Vessel	2406.1	N	1.59	0.11	0.29	0.25	0.07	0.56	123.70	0.92	0.010	0.020	1.2	Majewski	N	N	N
Cryostat Seals	4.4	Y	103.60	103.60	34.34	34.34	6.88	22.65	24.62	0.70	0.002	0.003	1.2	Majewski	N	N	N
Cryostat Insulation	23.8	Y	18.91	18.91	3.45	3.45	1.97	51.65	69.82	0.82	0.006	0.007	1.2	Majewski	N	N	N
Cryostat Teflon Liner	70.7	N	0.02	0.02	0.01	0.01	0.00	0.10	4.92	0.00	0.000	0.000	1.5	Saba	N	N	N
Outer Detector Tanks	4007.0	Y	0.15	0.37	0.02	0.06	0.04	4.28	93.19	0.14	0.000	0.001	1.6	Kyre	N	N	N
Liquid Scintillator	20789.3	Y	0.01	0.01	0.01	0.01	0.00	0.00	16.83	0.00	0.000	0.000	1.6	Nelson	N	N	N
Outer Detector PMTs	122.4	Y	1.507	1.507	1.065	1.065	0	3.900	14.539	0.08	0.058	0.079	1.6	Nelson	N	N	N
Outer Detector PMT Supports	770.0	N	1.20	0.27	0.33	0.49	1.60	0.40	14.30	0.31	0.000	0.000	1.6	Kyre	N	N	N
222Rn (0.67 mBq)										39.14	-	-	1.4	Hall			
220Rn (0.07 mBq)										6.43	-	-	1.4	Hall			
natKr (0.015 ppt g/g)										24.51	-	-	1.4	Hall			
natAr (0.45 ppb g/g)										2.47	-	-	1.4	Hall			
Subtotal (Non-v counts)										85.85	0.185	0.306					

- 1.10 working closely with cognizant engineers and managers to ensure table of materials and design is followed.
- Procurement of TPC elements roughly establishes the critical path for assay
- Including ^{210}Pb assays for critical components, SF veto is now implemented
- More on this and the assay 'score card' later in the review



Boulby Lab Move

- Looking like this will happen late Feb/early March
- We must be in and ready to go by end March
- Lab committed to this and also to postponing switch-off to last possible moment
- Air-con chiller (biggest potential problem) now underground





PMT Materials (detail)

Name	U-early mBq/kg	U-late mBq/kg	Th-early mBq/kg	Th-late mBq/kg	⁶⁰ Co mBq/kg	⁴⁰ K mBq/kg	Ref	Detector ¹
Faceplate	11	0.63	0.98	0.80	0.15	0.41	LZ	Maeve
Al seal	75.0	1.00	2.55	2.55	1.0	7.9	LZ	SOLO
Body	17.9	0.90	1.7	1.3	0.9	6.4	LZ	Maeve
Electrode	161.2	3.8	8.	8.	4.8	10.1	LZ	SOLO
Dynode	80.0	3.	5.	5.75	2.5	6.75	LZ	SOLO
Shield	106.9	1.9	4.2	2.8	1.8	7.6	LZ	SOLO
L-insulator	21	1	1.6	1.2	0.16	6.3	LZ	Maeve
FB flange	108	3.1	4.4	3.9	8.3	13.9	LZ	SOLO
Stem	105.7	19.98	7.77	7.53	1.	123.	LZ	Chaloner
Stem Flange	110.	1.80	3.2	2.1	9.3	5.7	LZ	SOLO
Getter	3020	61.4	161	161	50	1379286	LZ	SOLO
Cr ₂ O ₃ ²	26.57	98.62	8.4	9.29	3.12	74.19	LZ	Chaloner
Mass Weighted Average ³	57.15 84.52	2.94 4.23	2.94 3.90	2.53 3.01	2.52 3.47	16.56 13.77	LZ X-1T	

¹ best value, does not show confirming assays

² not included in mass weighted average

³ most values are upper limits



ICP-MS & GDMS

- Access to UA's (and others) in-house and commercial MS
- UCL has in-house system owned by 1.10 and dedicated to LZ assays
- Will be used verify most materials for direct U/Th progenitor content
- Used PNNL to verify LS and Ti so far





UCL ICP-MS lab

- Agilent 7900 ICP-MS + HF capability
- New ISO Class 6 (1000) cleanroom (ISO class 5 (100) laminar flow unit)
- Microwave digestion and ashing systems for sample prep
- ICP-MS system moved to new lab and sample preparation and auxiliary systems commissioned Oct. 15
- System operating at design sensitivity
- Resources:
 - 2.0 FTE PDRA, 0.5 FTE PGrad, 0.1 FTE detector physicist

Project milestones:

- **ICP-MS cleanroom commissioned: 18 Nov 15**
- **ICP-MS U/Th assay on digested sample: 21 Dec 15**



Milestone EthosUP digestion system



Pyro-260 microwave ashing system (PTFE, acrylics)



Crystal Types

P-type

- ~50-3000 keV
- Coaxial germanium detector
- N-type contact (diffused lithium) on the outer surface, and a p-type contact (ion implanted boron) on the surface of an axial well
- N-type contact is 0.5 mm and p-type contact is 0.3 μm
- The germanium has a net impurity level of $\sim 10^{10}$ atoms/cc, with moderate reverse bias, the entire volume between the electrodes is depleted, and an electric field extends across this active region

N-type

- ~3-3000 keV
- Coaxial detector with electrodes opposite conventional coaxial detectors
- P-type on outside, n-type is on the inside
- Outside contact is extremely thin, so can cover low energy down to 3 keV
- Outside contact collects holes, radiation damage resistant

Broad Energy Germanium (BeGe)

- ~3-3000 keV
- Cylindrical crystal that sits on pin
- Short fat shape that greatly enhances efficiency at low energies

Well

- ~20-3000 keV
- Provides maximum efficiency for small samples
- Small sample is placed in hole and surrounded by active detector material